



Aircom Supra LED

RGBW

Downlight LED



Grado de protección / Protection degree / IP44

Aircom Supra LED RGBW para mando Ref. 4500
Aircom Supra LED RGBW to controlled Ref. 4500



Incluye driver y lámparas LED / Includes driver and LED lamp

Ref.	Color / Colour	Lamp.	W
4228 01 60 85 4500	Blanco / White	LED RGBW	60w
4228 02 60 85 4500	Negro / Black	LED RGBW	60w
4228 03 60 85 4500	Dorado / Gold	LED RGBW	60w
4228 05 60 85 4500	Cromo / Chrome	LED RGBW	60w
4228 33 60 85 4500	Dorado mate / Matt Gold	LED RGBW	60w
4228 52 60 85 4500	Cromo mate / Matt Chrome	LED RGBW	60w
4228 55 60 85 4500	Niquel mate / Nickel	LED RGBW	60w
4228 57 60 85 4500	Niquel rayado / Nickel matt	LED RGBW	60w
4228 80 60 85 4500	Satinado / Satin	LED RGBW	60w
4228 90 60 85 4500	Titanio / Titanium	LED RGBW	60w

* No incluye mando / control not included.

Aircom Supra LED RGBW para mando Ref. 4501
Aircom Supra LED RGBW to controlled Ref. 4501



Incluye driver y lámparas LED / Includes driver and LED lamp

Ref.	Color / Colour	Lamp.	W
4228 01 60 85 4501	Blanco / White	LED RGBW	60w
4228 02 60 85 4501	Negro / Black	LED RGBW	60w
4228 03 60 85 4501	Dorado / Gold	LED RGBW	60w
4228 05 60 85 4501	Cromo / Chrome	LED RGBW	60w
4228 33 60 85 4501	Dorado mate / Matt Gold	LED RGBW	60w
4228 52 60 85 4501	Cromo mate / Matt Chrome	LED RGBW	60w
4228 55 60 85 4501	Niquel mate / Nickel	LED RGBW	60w
4228 57 60 85 4501	Niquel rayado / Nickel matt	LED RGBW	60w
4228 80 60 85 4501	Satinado / Satin	LED RGBW	60w
4228 90 60 85 4501	Titanio / Titanium	LED RGBW	60w

* No incluye mando / control not included.


Aircom Supra LED RGBW para mando Ref. 4502
Aircom Supra LED RGBW to controlled Ref. 4502



Incluye driver y lámparas LED / Includes driver and LED lamp

Ref.	Color / Colour	Lamp.	W
4228 01 60 85 4502	Blanco / White	LED RGBW	60w
4228 02 60 85 4502	Negro / Black	LED RGBW	60w
4228 03 60 85 4502	Dorado / Gold	LED RGBW	60w
4228 05 60 85 4502	Cromo / Chrome	LED RGBW	60w
4228 33 60 85 4502	Dorado mate / Matt Gold	LED RGBW	60w
4228 52 60 85 4502	Cromo mate / Matt Chrome	LED RGBW	60w
4228 55 60 85 4502	Niquel mate / Nickel	LED RGBW	60w
4228 57 60 85 4502	Niquel rayado / Nickel matt	LED RGBW	60w
4228 80 60 85 4502	Satinado / Satin	LED RGBW	60w
4228 90 60 85 4502	Titanio / Titanium	LED RGBW	60w

* No incluye mando / control not included.



Ref. 4500
Mando de control RGBW empotrable de pared por DMX.
RGBW Controller, Wall recessed by DMX.



Ref. 4501
Mando de control RGBW empotrable de pared por radiofrecuencia.
RGBW Controller, Wall recessed by radio frequency.



Ref. 4502
Mando para control RGBW portátil inalámbrico por radiofrecuencia.
RGBW controller portable wireless by Radio Frequency.

Incremento respecto accesorios / Rough price increase of accessories

Ref. 4500	Mando de control RGBW empotrable de pared por DMX RGBW Controller, Wall recessed by DMX
Ref. 4501	Mando de control RGBW empotrable de pared por radiofrecuencia RGBW Controller, Wall recessed by Radio Frequency
Ref. 4502	Mando para control RGBW portátil inalámbrico por radiofrecuencia RGBW controller portable wireless by Radio Frequency
Ref. IP65	Índice de protección IP65 / Protection degree IP65

Downlight LED RGBW para instalaciones exteriores, o para instalaciones interiores, su diseño elegante permite su adaptabilidad a cualquier ambiente. Gracias a su gran luminosidad, conseguida a partir de LEDs de color rojo, verde, azul y blanco, permite que esta luminaria pueda ser utilizada para iluminación decorativa en numerosos lugares. El control de color puede hacerse mediante varias opciones:

- Mando de control táctil empotrable DMX alimentado mediante un driver de 12V que debe estar alimentado a 230V, controla el proyector mediante un cable con señal DMX.
- Mando de control táctil empotrable por radiofrecuencia alimentado mediante un driver de 12V que debe estar alimentado a 230V, controla el proyector de manera inalámbrica.
- Mando de control táctil portátil por radiofrecuencia alimentado mediante 3 pilas, controla el proyector de manera inalámbrica.

Los equipos necesarios para la recepción de señal de los mandos se suministran en una caja estanca, externa al proyector.

RGB LED Downlight for outdoor or indoor facilities, the elegant design allows their adaptability to any environment. Thanks to its high brightness, obtained from LEDs red, green, blue and white colours, this luminaire can be used to decorative lighting in many places. The colour control can be done by several methods:

- Recessed DMX touch screen control powered by a 12V driver, supplied with 230V, the projector is controlled by a wire with DMX signal.
- Recessed radiofrequency touch screen control powered by a 12V driver supplied with 230V, the projector is controlled by wireless.
- Remote radiofrequency touch screen control supplied by 3 batteries, the projector is controlled by wireless.

The equipment required for the signal reception control will be supplied in a waterproof case, external to the projector.



secom
here comes the light

Polígono Industrial la Estrella. C/ Marte 18-21
0500 Molina de Segura (Murcia) Spain - Buzón de correos nº11
Tlf.: 968 80 12 11 - Fax.:968 89 10 48 - secom@secom.es
Dpto.Exportación. Tlf.: ++34-968-80 18 00. Fax.: ++34-968-89 10 48
export@secom.es



www.secom.es