

secom
here comes the light



CEIPRO C1/C2/C3

Empotrable de techo o pared
Recessed ceiling or wall



Empotrable de techo o pared Recessed ceiling or wall



Ceipro C1 LED circular



Ceipro C1 LED circular

Incluye driver y lámpara LED Duris E5 2w
Includes driver and LED Duris E5 lamp 2w

Ref.	Color / Colour	Lamp.	W	lum.
5100 00 02 84	A. Inox. / Stainless steel / 316	LED	2w	150

* Se suministra de manera estándar con ángulo de máxima apertura (120°) / * Standardly supplied with maximum lamp opening angle (120°).
* Se suministra de manera estándar con lámpara 4000°K. / * Standardly supplied with 4000°K lamp.

OPCIONES COLOR LEDs / LEDs COLOUR OPTIONS

Rojo / Red ● - Verde / Green ● - Azul / Blue ●

OPCIONES / OPTIONS LED	Ref. 83	Ref. 84	Ref. 85
CRI>80 / Temp. de color / Colour temperature	3000°K	4000°K	5700°K
Lum 2w	140	150	150

Incremento por accesorios / Rough price increase accessories

Ref. CMZ1 Cristal mate / Matt glass

Ceipro C2 LED circular



Ceipro C2 LED orientable circular / adjustable circular

Incluye driver y lámpara LED Oslon SSL / Includes driver and LED Oslon SSL

Ref.	Color / Colour	Lamp.	W	lum.
5120 00 06 84	A. Inox. / Stainless steel / 316	LED	6w	650
5120 00 10 84	A. Inox. / Stainless steel / 316	LED	10w	1170

Ceipro C2 LED orientable asimétrico circular / asymmetric adjustable circular



Incluye driver y lámpara LED Oslon SSL / Includes driver and LED Oslon SSL

Ref.	Color / Colour	Lamp.	W	lum.
5110 00 07 84	A. Inox. / Stainless steel / 316	LED	7w	780

* Se suministra de manera estándar con ángulo de máxima apertura (48°) / * Standardly supplied with maximum lamp opening angle (48°).
* Se suministra de manera estándar con lámpara 4000°K. / * Standardly supplied with 4000°K lamp.

OPCIONES COLOR LEDs / LEDs COLOUR OPTIONS

Rojo / Red ● - Verde / Green ● - Azul / Blue ●

OPCIONES / OPTIONS LED	Ref. 83	Ref. 84	Ref. 85
CRI>80 / Temp. de color / Colour temperature	3000°K	4000°K	5000°K
Lum 6w	605	650	700
Lum 7w asimétrico / asymmetric	726	780	840
Lum 10w	1089	1170	1260

Incremento por accesorios / Rough increase of accessories

Ref. 11 Ángulo de apertura 11° / Opening angle 11°

Ceipro C2 LED cuadrado / square



Ceipro C2 LED orientable cuadrado / adjustable square

Incluye driver y lámpara LED Oslon SSL / Includes driver and LED Oslon SSL

Ref.	Color / Colour	Lamp.	W	lum.
5130 00 06 84	A. Inox. / Stainless steel / 316	LED	6w	650
5130 00 10 84	A. Inox. / Stainless steel / 316	LED	10w	1170

Ceipro C2 LED orientable asimétrico cuadrado / asymmetric adjustable square



Incluye driver y lámpara LED Oslon SSL / Includes driver and LED Oslon SSL

Ref.	Color / Colour	Lamp.	W	lum.
5140 00 07 84	A. Inox. / Stainless steel / 316	LED	7w	780

* Se suministra de manera estándar con ángulo de máxima apertura (48°) / * Standardly supplied with maximum lamp opening angle (48°).
* Se suministra de manera estándar con lámpara 4000°K. / * Standardly supplied with 4000°K lamp.

OPCIONES COLOR LEDs / LEDs COLOUR OPTIONS

Rojo / Red ● - Verde / Green ● - Azul / Blue ●

OPCIONES / OPTIONS LED	Ref. 83	Ref. 84	Ref. 85
CRI>80 / Temp. de color / Colour temperature	3000°K	4000°K	5000°K
Lum 6w	605	650	700
Lum 7w asimétrico / asymmetric	726	780	840
Lum 10w	1089	1170	1260

Incremento por accesorios / Rough increase of accessories

Ref. 11 Ángulo de apertura 11° / Opening angle 11°

Empotrable de techo o pared

Recessed ceiling or wall

Ceipro C3 LED circular



Ceipro C3 LED orientable circular / adjustable circular

Incluye driver y lámpara LED Oslon SSL / Includes driver and LED Oslon SSL

Ref.	Color / Colour	Lamp.	W	lum.
5150 00 20 84	A. Inox. / Stainless steel / 316	LED	20w	2340
5150 00 30 84	A. Inox. / Stainless steel / 316	LED	28w	4420



Ceipro C3 LED orientable asimétrico circular / asymmetric adjustable circular

Incluye driver y lámpara LED Oslon SSL / Includes driver and LED Oslon SSL

Ref.	Color / Colour	Lamp.	W	lum.
5180 00 22 84	A. Inox. / Stainless steel / 316	LED	22w	2600



* Se suministra de manera estándar con ángulo de máxima apertura (48°) / * Standardly supplied with maximum lamp opening angle (48°).
* Se suministra de manera estándar con lámpara 4000°K. / * Standardly supplied with 4000°K lamp.

OPCIONES COLOR LEDs / LEDs COLOUR OPTIONS

Rojo / Red ● - Verde / Green ● - Azul / Blue ●

OPCIONES / OPTIONS LED	Ref. 83	Ref. 84	Ref. 85
CRI>80 / Temp. de color / Colour temperature	3000°K	4000°K	5000°K
Lum 20w	2178	2340	2520
Lum 22w asimétrico / asymmetric	2420	2600	2800
Lum 28w	3085	3315	3570

Incremento por accesorios / Rough increase of accessories

Ref. 11 Ángulo de apertura 11° / Opening angle 11°

Ceipro C3 LED cuadrado / square



Ceipro C3 LED orientable cuadrado / adjustable square

Incluye driver y lámpara LED Oslon SSL / Includes driver and LED Oslon SSL

Ref.	Color / Colour	Lamp.	W	lum.
5160 00 18 84	A. Inox. / Stainless steel / 316	LED	18w	2080
5160 00 30 84	A. Inox. / Stainless steel / 316	LED	30w	4680



Ceipro C3 LED orientable asimétrico cuadrado / asymmetric adjustable square

Incluye driver y lámpara LED Oslon SSL / Includes driver and LED Oslon SSL

Ref.	Color / Colour	Lamp.	W	lum.
5170 00 20 84	A. Inox. / Stainless steel / 316	LED	20w	2340



* Se suministra de manera estándar con ángulo de máxima apertura (48°) / * Standardly supplied with maximum lamp opening angle (48°).
* Se suministra de manera estándar con lámpara 4000°K. / * Standardly supplied with 4000°K lamp.

OPCIONES COLOR LEDs / LEDs COLOUR OPTIONS

Rojo / Red ● - Verde / Green ● - Azul / Blue ●

OPCIONES / OPTIONS LED	Ref. 83	Ref. 84	Ref. 85
CRI>80 / Temp. de color / Colour temperature	3000°K	4000°K	5000°K
Lum 18w	1936	2080	2240
Lum 20w asimétrico / asymmetric	2178	2340	2520
Lum 30w	3267	3510	3780

Incremento por accesorios / Rough increase of accessories

Ref. 11 Ángulo de apertura 11° / Opening angle 11°

Empotrable de techo o pared

Ceipro C1 / C2 / C3 LED

Grado de protección IP67 / IK10

- Material:** Acabado en acero inoxidable AISI 316. Cuerpo de la luminaria en plástico inyectado para el C1 y aluminio inyectado para el C2 y C3. Incluye cristal templado protector con una resistencia de hasta 5000Kg.
- Óptica:** Incorporada en la lámpara, con un ángulos de apertura de 120° para C1 y 48° o 11° para C2 y C3.
- Alimentación:** Todos los modelos incluyen equipos y lámparas adecuados.
- Lámparas:** LEDs Osram, Duris E5 para C1 y Oslon SSL para C2 / C3.
- Instalación:** Corte de techo circular. Adaptable a todo tipo de techos modulares y de escayola, para empotrar en falso techo mediante pinzas de sujeción. Opción de caja auxiliar para empotrar en obra de cemento o hormigón.
- Colores:** Acero inoxidable.

Recessed ceiling or wall

Ceipro C1 / C2 / C3 LED

Protection degree IP67 / IK10

- Material:** Finished in stainless steel 316. Body of the luminaire made in injected plastic in C1, injected aluminium in C2 and C3. It includes a protection tempered glass which have 5000kg resistance.
- Óptica:** Integrated in the lamps, with opening angles of 120° for C1 and 48 ° or 11 ° for C2 and C3.
- Supply:** All models include control gear and lamps.
- Lamps:** LEDs Osram, Duris E5 for C1 and Oslon SSL for C2 / C3.
- Installation:** Circular ceiling cut. For recessed ceiling, adaptable to all kind of modular ceilings and plaster. Clamps included. Auxiliary flush housing option for recessing in cement or concrete work.
- Colours:** Stainless steel.

Módulos orientables para Ceipro C2 y Ceipro C3, presionando o girando sobre la placa de LEDs.

Adjustable modules for Ceipro C2 and Ceipro C3, pressing or turning on the LEDs PCB.



Simétrico / Symmetric



Asimétrico / Asymmetric

Empotrable de techo o pared / Recessed ceiling or wall

Ceipro C1 LED circular



Ceipro C2 LED circular - cuadrado/square

Ceipro C3 LED circular - cuadrado/square



1 conector IP67
1 connector IP67






Pinzas de sujeción.
Clamps.



2 conectores IP67, uno de entrada y otro de salida.
2 connectors IP67, one input and one output.

Válvula anticondensación.
Anti-condensation valve.






Pinzas de sujeción.
Clamps.



2 conectores IP67, uno de entrada y otro de salida.
2 connectors IP67, one input and one output.

Válvula anticondensación.
Anti-condensation valve.

Pinzas de sujeción.
Clamps.



Polígono Industrial La Estrella. C/ Marte 18-21.
30500 Molina de Segura. Murcia. Spain
Tlf. 968 80 12 11 / Fax 968 89 10 48
secom@secom.es

Dpto. Exportación.
Tlf. ++34-968-80 18 00
Fax. ++34-968-89 10 48
export@secom.es



www.secom.es

